

SABINE RIVER AUTHORITY OF TEXAS

TO: INTERESTED PARTIES
FROM: ENVIRONMENTAL SERVICES DIVISION
RE: JUNE 2019 MONTHLY WATER QUALITY REPORT

The Environmental Services Field Offices conducted water quality monitoring in the Sabine Basin from June 10th through the 13th. The results of field monitoring are presented in this report¹ and additional data can be found using the Texas Commission on Environmental Quality (TCEQ) [Clean Rivers Program Data Tool](#).

Sabine Basin Tidal (Including Tributaries)

Weather – Air temperatures in the tidal basin were warm with highs in the mid 70s to low 90s. Low temperatures were in the upper 60s to low 70s. The tidal stations received 4.42 inches of rainfall in the seven days prior to the sampling event.

Tidal Conditions – Surface salinity values were not greater than 2 ppt at any of the six tidal stations. The greatest salinity value of 0.3 ppt was recorded at station 15654 (BB1) throughout the water column.

Lower Sabine Basin (Toledo Bend Reservoir and the Sabine River downstream to Tidal)

Weather – Air temperatures in the lower basin were warm with highs in the upper 80s. Low temperatures ranged in the upper 60s to low 70s. Toledo Bend received 0.83 inches of rainfall during the seven days prior to the sampling event.

Lake Level - The level of Toledo Bend was 171.6 feet with a daily average discharge of 12,573 cfs on the day of sampling. Toledo Bend has a conservation pool level of 172 feet msl. Reservoir profiles indicated stratification of the water column.

Upper Sabine Basin (Lake Tawakoni, Lake Fork Reservoir, and the Sabine River upstream of Toledo Bend)

Weather - Air temperatures in the upper basin were warm with highs in the upper 70s to upper 80s. Low temperatures were in the low 60s to low 70s. Lake Fork and Lake Tawakoni received 0.45 and 1.37 inches of rainfall, respectively, during the seven days prior to the sampling event.

Lake Level - The level of Lake Tawakoni was 438.03 feet msl with a release of 500 cfs on the day of sampling. The level of Lake Fork was 403.11 feet msl with a 20 cfs release on the day of sampling. Lake Tawakoni and Lake Fork have conservation pool levels of 437.5 feet msl and 403 feet msl, respectively. Reservoir profiles at Lake Tawakoni and Lake Fork indicated stratification of the water column.

This report and additional links to data for these monitoring stations are available at the [Sabine River Authority of Texas website](#). If you have any questions or comments concerning this report, please contact:

- Debra Malus, Environmental Services Division Manager
409-746-3284 (dmalus@srtx.org)
- *Lower and Tidal Sabine Basin*
Jerry Wiegreffe, Lower Basin Field Office Coordinator
409-746-3284 (jwiegreffe@srtx.org)
- *Upper Sabine Basin*
Terry Wilson, Upper Basin Field Office Coordinator
903-878-2420 (twilson@srtx.org)

¹ Data in this report is considered preliminary until it is available in TCEQ's Surface Water Quality Monitoring Information System database.

SABINE RIVER AUTHORITY OF TEXAS
Monthly Water Quality Report


Table of Contents

Fixed Monitoring Stations	4
Segment 0501 – Sabine River Tidal.....	5
Segment 0502 - Sabine River Above Tidal.....	7
Segment 0503 - Sabine River Above Caney Creek	8
Segment 0504 – Toledo Bend Reservoir.....	9
Segment 0505 - Sabine River Above Toledo Bend Reservoir	14
Segment 0506 - Sabine River Below Lake Tawakoni	15
Segment 0507 - Lake Tawakoni	19

Table of Figures

Sabine Basin Map	3
Segment 0501	6
Segment 0502.....	7
Segment 0503	8
Toledo Bend Reservoir Profiles	12
Segment 0504.....	13
Segment 0505	14
Lake Fork Reservoir Profiles.....	17
Segment 0506	18
Lake Tawakoni Reservoir Profiles	20
Segment 0507	21

Sabine Basin Map



Current Fixed Monitoring Stations

Segment	Station TCEQ ID (SRA-TX ID)	Location
501	10391 (SRT1)	SABINE RIVER AT CHANNEL CAN 3
501	15654 (BB1)	BLACK BAYOU IN CAMERON PARISH
511	10449 (CB1)	COW BAYOU AT ROUND BUNCH ROAD
508	10441 (AB2)	ADAMS BAYOU AT FM 1006
501	15653 (ICW1)	INTERCOASTAL WATERWAY AT PERRY RIDGE
501	10394 (SRT2)	SABINE RIVER AT IH 10
502	10395 (SR1)	SABINE RIVER 12.00 KM UPSTREAM OF IH 10
502	10397 (SR2)	SABINE RIVER AT SH 12 NORTH OF DEWEYVILLE TX.
513	10465 (BCC1)	BIG COW CREEK AT FM 1416 SOUTH OF BON WIER
503	10398 (SR3)	SABINE RIVER AT US 190 EAST OF BON WIER TX.
503	10340 (BA4)	ANACOCO BAYOU AT LOUISIANA HWY 111 CROSSING SOUTHWEST OF KNIGHT LA.
503	10399 (SR5)	SABINE RIVER AT SH 63 EAST OF BURKEVILLE TX.
503	10401 (TB6S)	SABINE RIVER BELOW TOLEDO BEND RESERVOIR AT RIGHT ABUTMENT OF SPILLWAY FOR DAM
503	15660 (BT1)	BAYOU TORO AT LA SH 392 IN SABINE PARISH SW OF HORNBECK LA.
504	10404 (TB6A)	TOLEDO BEND RESERVOIR MAIN LAKE ABOVE THE DAM AT THE OLD RIVER CHANNEL
504	10406 (TB6C)	TOLEDO BEND RESERVOIR IN SIX MILE BOAT LANE 0.8KM EAST OF SH 87
504	18054 (TB6Q)	TOLEDO BEND RESERVOIR IN NEGREET BAYOU
504	10411 (TB6F)	TOLEDO BEND RESERVOIR IN SUNSHINE BAY NEAR FM 3121 BRIDGE
504	10402 (TB6H)	TOLEDO BEND RESERVOIR AT SH 21 NORTHEAST OF MILAM
504	15659 (TB6K)	TOLEDO BEND RESERVOIR IN LANANA BAYOU AT LOUISIANA SH 191 IN SABINE PARISH LOUISIANA WEST OF MANY
504	15655 (TB6J)	TOLEDO BEND RESERVOIR PATROON BAYOU BRANCH AT FM 276
504	18053 (TB6LN)	TOLEDO BEND RESERVOIR SAN MIGUEL ARM BOAT LANE
504	18052 (TB6R)	TOLEDO BEND RESERVOIR AT RAGTOWN
505	10415 (SR10)	SABINE RIVER AT FM 2517
505	13628 (SR11)	SABINE RIVER AT US 59
505	10427 (SR16)	SABINE RIVER AT SH 42
506	10428 (SR17)	SABINE RIVER AT US 271
506	10429 (SR19)	SABINE RIVER AT SH 14 S. OF HAWKINS
506	10430 (SR21)	SABINE RIVER AT US 69
514	10468 (BS1)	BIG SANDY CREEK AT SH 155
515	10469 (LF20)	LAKE FORK CREEK AT US 80
512	10458 (LF2)	LAKE FORK RESERVOIR NEAR DAM IN CREEK CHANNEL
512	10462 (LF4)	LAKE FORK RESERVOIR MID-COVE IN LAKE FORK CREEK ARM AT FM 515
512	10461 (LF3)	LAKE FORK RESERVOIR MID-ARM IN CANEY CREEK ARM AT FM 515
507	10434 (LT23A)	LAKE TAWAKONI IN THE MAIN LAKE NEAR THE DAM
507	21173 (LT23DN)	LAKE TAWAKONI IN WACO BAY EQUIDISTANT FROM FINGER AND SPRING POINTS 1.17KM BEARING 18.61 DEGREES FROM IRON BRIDGE PUMPING STATION
507	10437 (LT23B)	LAKE TAWAKONI AT SH 276

Segment 0501 – Sabine River Tidal

Description: The designated segment includes the Sabine River from the confluence with Sabine Lake in Orange County to West Bluff in Orange County. Although some areas are quite rural, this part of the Sabine Basin has two cities with populations greater than 5,000 and a variety of industries.


Segment 0508 – Adams Bayou Tidal. The segment reaches from the confluence with the Sabine River in Orange County to a point 1.1 kilometers (0.7 miles) upstream of IH-10 in Orange County.

Segment 0511 – Cow Bayou Tidal. The segment reaches from the confluence with the Sabine River in Orange County to a point 4.8 kilometers (3.0 miles) upstream of IH-10 in Orange County.

Segment 0501 Water Quality

Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond μS/cm	TDS mg/L	Salinity ppt	Secchi meters	Turbidity NTU	Enterococcus mpn/ 100mL
6/13/19 09:55	10391(SRT1)	0.3	26.5	6.4	5.0	62	119	76	<0.1	0.54	22.8	10
		3.0	26.5	5.8	4.9	61	118	76	<0.1			
		6.0	26.5	6.0	4.9	60	118	76	<0.1			
		9.0	26.5	6.1	4.8	60	118	76	<0.1			
6/13/19 09:35	15654(BB1)	0.3	28.5	6.6	4.5	58	556	356	0.3	0.64	11.5	74
		1.5	28.5	5.8	4.5	57	556	356	0.3			
		3.0	28.5	6.0	4.4	56	556	356	0.3			
Segment 0511												
6/13/19 12:25	10449(CB1)	0.3	28.2	5.8	3.3	42	62	40	<0.1	0.33	29.3	98
		2.0	28.1	5.0	3.2	41	62	40	<0.1			
		4.0	28.1	5.1	3.2	41	62	40	<0.1			
Segment 0508												
6/13/19 10:15	10441(AB2)	0.3	28.1	6.2	2.3	30	109	70	<0.1	0.49	14.6	63
		2.0	27.9	5.5	2.0	26	109	70	<0.1			
		4.0	27.8	5.7	1.9	25	109	70	<0.1			
6/13/19 10:30	15653(ICW1)	0.3	27.3	6.3	5.0	63	113	72	<0.1	0.57	17.6	10
		3.0	27.1	5.8	5.0	62	113	72	<0.1			
		6.0	27.0	6.0	4.8	60	114	73	<0.1			
6/13/19 11:00	10394(SRT2)	0.3	26.2	6.4	5.1	63	115	74	<0.1	0.38	31.0	98
		3.0	26.2	5.9	5.0	62	115	74	<0.1			
		6.0	26.2	6.1	5.0	62	115	74	<0.1			
		8.0	26.2	6.2	5.0	62	115	74	<0.1			

Segments 0501, 0508 & 0511



Segment 0502 - Sabine River Above Tidal

Description: The designated segment includes the Sabine River from West Bluff in Orange County to the confluence with Caney Creek in Newton County. The largest tributary is Big Cow Creek (Segment 0513). This is largely a rural area with no major industries or cities.

Segment 0513 – Big Cow Creek. The segment reaches from the confluence with the Sabine River in Newton County to a point 4.6 kilometers (2.9 miles) upstream of CR 255 in Newton County.


Segment 0502 USGS Recorded Flows

Date and Time	Station	USGS Station #	Location	Flow (cfs)
6/12/19 08:30	10397(SR2)	08030500	Sabine River near Ruliff, TX	15,300

Segment 0502 Water Quality

Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond µS/cm	TDS mg/L	Secchi meters	Turbidity NTU	E.coli mpn/100mL
6/12/19 11:35	10395(SR1)	0.3	26.8	6.6	5.3	66	136	87	0.36	38.2	12
6/12/19 08:30	10397(SR2)	0.3	27.3	6.6	5.6	70	111	71	0.51	26.8	18
Segment 0513											
6/12/19 09:15	10465(BCC1)	0.3	23.7	6.0	7.1	84	32	20	0.41	22.6	32

Segments 0502 & 0513



Segment 0503 - Sabine River Above Caney Creek

Description: The designated segment includes the Sabine River from a point immediately upstream of the confluence with Caney Creek in Newton County up to Toledo Bend Dam in Newton County. This is largely a rural area with one major city with a population greater than 5,000 and few industries. Two major tributaries that flow from Louisiana include Bayou Anacoco and Bayou Toro.


Segment 0503 USGS Recorded Flows

Date and Time	Station	USGS Station #	Location	Flow (cfs)
6/12/19 11:08	10398(SR3)	08028500	Sabine River near Bon Wier, TX	15,300
6/12/19 10:15	10399(SR5)	08026000	Sabine River near Burkeville, TX	14,100

Segment 0503 Water Quality

Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond µS/cm	TDS mg/L	Secchi meters	Turbidity NTU	E.coli mpn/100mL
6/12/19 11:08	10398(SR3)	0.3	28.5	7.1	7.4	96	117	75	0.45	11.1	1
6/12/19 10:45	10340(BA4)	0.3	27.4	6.9	6.7	85	197	126	0.36	24.3	3
6/12/19 10:15	10399(SR5)	0.3	28.2	7.2	7.5	96	114	73	0.91	4.85	<1
6/11/19 13:20	10401(TB6S)	0.3	24.3	6.7	8.7	104	109	70	1.1	4.98	13
6/10/19 13:20	15660(BT1)	0.3	27.3	6.0	7.0	89	68	43	0.69	21.5	28

Segment 0503



Segment 0504 – Toledo Bend Reservoir

Description: The designated segment includes the Sabine River from Toledo Bend Dam in Newton County to a point immediately upstream of the confluence of Murvaul Creek in Panola County. Although this area is largely rural, it includes two cities with populations greater than 5,000. Murvaul Creek is a major tributary that enters upstream of the reservoir.

Segment 0504 Water Quality


Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond µS/cm	TDS mg/L	Secchi meters	Turbidity NTU	E.coli mpn/100mL
6/11/19 13:47	10404(TB6A)	0.3	29.4	8.1	8.5	111	115	74	1.3	3.59	2
		1.0	29.3	7.4	8.5	111	115	74			
		2.0	28.8	7.3	8.5	109	115	74			
		3.0	28.7	7.2	8.0	102	115	74			
		4.0	28.6	7.1	7.8	100	114	73			
		5.0	28.6	7.2	7.8	100	114	73			
		8.0	28.5	7.2	7.8	100	114	73			
		11.0	25.6	6.9	3.4	38	111	71			
		14.0	19.7	6.6	1.5	16	96	61			
		17.0	16.9	6.4	0.6	6	98	62			
		20.0	16.5	6.4	0.2	2	99	63			
		23.0	16.0	6.3	0.1	1	97	62			
		25.0	14.5	6.3	<0.1	<1	100	64			
6/11/19 08:20	10406(TB6C)	0.3	25.0	7.1	8.4	102	93	60	1.1	4.55	1
		1.0	25.0	6.6	8.4	102	93	60			
		2.0	25.1	6.7	8.3	100	96	62			
		3.0	23.9	6.7	8.6	103	98	60			
6/11/19 12:07	18054(TB6Q)	0.3	27.4	6.9	5.7	72	105	67	1.4	3.61	<1
		1.0	27.4	6.2	5.7	72	105	67			
		2.0	27.4	6.2	5.6	71	105	67			
		3.0	27.4	6.2	5.5	69	105	67			
		4.0	27.2	6.3	5.3	66	105	67			
		5.0	27.0	6.3	4.0	50	106	68			
		6.0	26.7	6.1	2.2	27	105	67			
		7.0	26.4	6.2	1.4	17	106	68			
		8.0	26.1	6.2	0.5	5	110	70			
		9.0	25.5	6.2	<0.1	<1	114	73			

Segment 0504 Water Quality Continued


Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond µS/cm	TDS mg/L	Secchi meters	Turbidity NTU	<i>E.coli</i> mpn/100mL
6/10/19 11:11	10411(TB6F)	0.3	29.5	7.2	8.4	111	78	50	0.85	4.38	5
		1.0	29.5	7.2	8.4	110	78	50			
		2.0	29.5	7.2	8.4	111	78	50			
		3.0	29.4	7.3	8.5	111	78	50			
		4.0	28.0	7.0	4.6	50	70	45			
		5.0	26.5	6.4	1.0	12	74	47			
6/11/19 09:30	10402(TB6H)	0.3	28.3	6.6	7.2	93	93	60	1.4	3.85	<1
		1.0	28.3	6.8	7.2	93	93	60			
		2.0	28.3	6.8	7.2	92	93	60			
		3.0	28.3	6.9	7.2	92	93	60			
		4.0	28.3	6.9	7.1	92	93	60			
		5.0	28.3	6.9	7.1	91	93	60			
		8.0	28.2	7.0	7.0	90	93	60			
		11.0	26.2	6.6	1.6	17	102	65			
		14.0	21.9	6.5	0.2	2	102	65			
		17.0	18.2	6.4	<0.1	<1	105	67			
		20.0	18.0	6.4	<0.1	<1	105	67			
		22.0	18.0	6.4	<0.1	<1	106	68			
6/10/19 11:40	15659(TB6K)	0.3	28.2	7.6	8.6	110	85	55	0.83	6.31	<1
		1.0	27.8	7.1	8.7	110	85	55			
		2.0	28.0	7.1	8.6	109	85	55			
		3.0	27.3	6.8	5.1	63	84	54			
		4.0	26.5	6.3	2.2	23	84	54			
		5.0	25.9	6.2	0.7	8	86	55			
		6.0	25.5	6.1	0.1	1	87	56			
		7.0	25.3	6.1	<0.1	<1	94	60			
		8.0	25.0	6.2	<0.1	<1	101	65			
		9.0	24.8	6.2	<0.1	<1	103	66			
6/10/19 10:45	15655(TB6J)	0.3	28.7	7.2	7.1	92	98	63	0.80	5.78	1
		1.0	28.7	6.6	7.1	92	98	63			
		2.0	28.6	6.6	7.0	90	98	63			
		3.0	28.6	6.7	6.9	89	98	63			
		4.0	28.5	6.7	6.8	87	98	63			
		5.0	27.3	6.4	1.2	15	104	67			

Segment 0504 Water Quality Continued


Toledo Bend Reservoir Profiles




TOLEDO BEND RESERVOIR MAIN LAKE ABOVE THE DAM AT THE OLD RIVER CHANNEL



TOLEDO BEND RESERVOIR AT SH 21 NORTHEAST OF MILAM



Segment 0504



Segment 0505 - Sabine River Above Toledo Bend Reservoir

Description: The designated segment includes the Sabine River from a point immediately upstream of the confluence of Murvaul Creek in Panola County to a point 100 meters (110 yards) downstream of US 271 in Gregg County. Segment 0505 is used extensively for water supply and contains the highest concentration of population in the Sabine Basin with eight cities having populations greater than 5,000. Segment 0505 includes a large section of the East Texas Oilfield as well as numerous industries.


Segment 0505 USGS Recorded Flows

Date and Time	Station	USGS Station #	Location	Flow (cfs)
6/12/19 09:45	13628(SR11)	08022040	Sabine River near Beckville, TX	9,110

Segment 0505 Water Quality

Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond µS/cm	TDS mg/L	Secchi meters	Turbidity NTU	<i>E. coli</i> mpn/100mL
6/12/19 09:58	10415(SR10)	0.3	25.6	6.9	5.9	73	148	95	0.12	32.7	8
6/12/19 09:45	13628(SR11)	0.3	25.3	6.9	5.7	70	157	100	0.27	25.6	14
6/12/19 08:15	10427(SR16)	0.3	25.0	6.8	4.1	50	174	111	0.28	14.7	30

Segment 0505



Segment 0506 - Sabine River Below Lake Tawakoni

Description: The designated segment includes the Sabine River from a point 100 meters (110 yards) downstream of US 271 in Gregg County to Iron Bridge Dam in Rains County. This is largely a rural area with no cities having a population greater than 5,000. Oilfield activities, rural housing developments, and agriculture are in the watershed. The major tributaries include:

Segment 0514 - Big Sandy Creek. The segment reaches from the confluence with the Sabine River in Upshur County to a point 2.6 kilometers (1.6 miles) upstream of SH 11 in Hopkins County.

Segment 0515 - Lake Fork Creek. The segment reaches from the confluence with the Sabine River in Wood County to Lake Fork Dam in Wood County.

Segment 0512 - Lake Fork Reservoir. The segment reaches from Lake Fork Dam in Wood County up to the normal pool elevation of 403 feet.

Segment 0506 USGS- Recorded Flows

Date and Time	Station	USGS Station #	Location	Flow (cfs)
6/12/19 09:58	10428(SR17)	08020000	Sabine River near Gladewater, TX	5,880
6/12/19 06:28	10429(SR19)	08019200	Sabine River near Hawkins, TX	2,270
6/11/19 14:24	10430(SR21)	08018500	Sabine River near Mineola, TX	1,500
Segment 0514				
6/12/19 07:05	10468(BS1)	08019500	Big Sandy Creek near Big Sandy, TX	182




Segment 0506 Water Quality

Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond µS/cm	TDS mg/L	Secchi meters	Turbidity NTU	E. coli mpn/100mL
6/12/19 09:58	10428(SR17)	0.3	25.0	6.8	4.1	50	175	112	0.31	21.3	30
6/12/19 06:28	10429(SR19)	0.3	25.0	7.1	5.5	68	195	125	0.12	29.7	23
6/11/19 14:24	10430(SR21)	0.3	26.0	7.3	5.3	6	199	127	0.17	29.1	25
Segment 0514											
6/12/19 07:05	10468(BS1)	0.3	23.2	6.8	6.2	72	124	79	0.28	22.1	91
Segment 0515											
6/11/19 14:55	10469(LF20)	0.3	25.2	6.6	5.4	67	187	119	0.17	33.5	28


Segment 0506 Water Quality Continued

Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond µS/cm	TDS mg/L	Secchi meters	Turbidity NTU	E. coli mpn/100mL
Segment 0512											
6/11/19 12:541	10458(LF2)	0.3	27.0	8.5	8.7	110	125	79	0.79	4.60	1
		1.0	26.9	8.5	8.7	110	125	79			
		2.0	26.8	8.6	8.5	106	125	79			
		3.0	26.6	7.9	7.8	98	125	79			
		4.0	26.6	7.8	7.7	97	125	79			
		5.0	26.6	7.8	7.7	97	125	79			
		8.0	25.2	7.3	3.8	45	125	79			
		11.0	20.0	6.7	0.8	8	129	83			
		14.0	17.8	6.6	0.3	3	136	87			
		17.0	16.8	6.6	0.1	1	146	93			
		18.0	16.6	6.8	0.1	1	160	103			
6/11/19 11:29	10462(LF4)	0.3	26.3	7.8	7.8	98	128	80	0.66	5.60	<1
		1.0	26.3	7.8	8.9	98	128	80			
		2.0	26.3	7.7	8.9	98	128	80			
		3.0	26.1	7.2	7.0	86	128	80			
		4.0	25.9	7.3	6.6	81	128	80			
		5.0	25.7	7.2	6.5	80	128	80			
		6.0	25.7	7.2	6.4	80	128	80			
		7.0	25.4	7.1	4.9	58	128	80			
		8.0	23.8	6.8	2.3	26	128	80			
		9.0	23.0	6.7	1.5	17	128	80			
		10.0	22.6	6.6	0.9	10	128	80			
		11.0	21.0	6.6	0.3	3	137	88			
6/11/19 12:00	10461(LF3)	0.3	26.4	8.3	8.6	107	127	81	0.54	6.00	1
		1.0	26.3	8.3	8.5	106	127	81			
		2.0	26.3	8.2	8.4	105	126	80			
		3.0	25.7	7.6	7.0	86	126	80			
		4.0	25.5	7.3	6.1	75	126	80			
		5.0	25.5	7.2	5.6	68	126	80			
		6.0	24.1	6.6	1.2	11	129	82			
		7.0	23.1	6.7	0.7	8	129	82			
		8.0	22.8	6.6	0.6	7	130	83			
		9.0	22.5	6.6	0.2	2	132	84			

Lake Fork Reservoir Profiles



Segments 0506, 0512, 0514 & 0515




Segment 0507 - Lake Tawakoni

Description: The designated segment includes the impounded Sabine River from Iron Bridge Dam in Rains County up to the normal pool elevation of 437.5 feet. Although much of this segment is rural, it contains two cities with populations greater than 5,000, and one of the four largest cities in the Sabine Basin.


Segment 0507 Water Quality

Date and Time	Station	Depth meters	Temp °C	pH SU	DO mg/L	% Sat	Cond µS/cm	TDS mg/L	Secchi meters	Turbidity NTU	E. coli mpn/100mL
6/11/19 10:12	10434(LT23A)	0.3	26.1	8.8	8.4	105	170	109	0.53	6.80	<1
		1.0	26.1	8.8	8.3	103	170	108			
		2.0	26.1	8.7	8.2	102	170	108			
		3.0	26.1	8.7	8.0	100	170	108			
		4.0	26.0	8.7	7.8	97	170	108			
		5.0	26.0	8.6	7.5	93	170	108			
		6.0	25.9	8.5	7.1	88	171	109			
		7.0	25.8	8.4	7.0	86	171	109			
		10.0	25.5	8.1	6.7	82	172	110			
		13.0	22.6	7.1	0.8	9	173	111			
		15.0	20.7	7.0	0.2	2	180	115			
6/11/19 09:34	21173(LT23DN)	0.3	26.3	8.7	8.4	105	170	109	0.44	8.80	1
		1.0	26.3	8.7	8.4	105	170	109			
		2.0	26.3	8.6	8.3	104	170	109			
		3.0	26.3	8.6	8.2	103	170	109			
		4.0	26.2	8.5	8.0	99	170	109			
		5.0	26.0	8.4	7.8	97	170	109			
		6.0	25.9	8.4	7.6	94	170	109			
		7.0	25.9	8.3	7.4	92	170	109			
		8.0	25.9	8.3	7.4	92	170	109			
		9.0	25.8	8.2	7.2	87	170	109			
		10.0	24.3	7.4	1.4	15	176	113			
6/11/19 09:07	10437(LT23B)	0.3	25.2	8.0	7.0	86	171	109	0.50	10.0	<1
		1.0	25.2	7.9	6.8	84	171	109			
		2.0	25.2	7.9	6.6	81	171	109			
		3.0	25.2	7.8	6.6	80	171	109			
		4.0	25.2	7.8	6.5	80	171	109			
		5.0	25.2	7.8	6.5	80	171	109			
		6.0	24.8	7.5	5.0	58	172	110			
		7.0	22.8	7.1	0.4	4	175	112			
		8.0	22.5	7.0	0.4	4	176	112			
		9.0	22.3	6.9	0.2	2	177	113			


Lake Tawakoni Reservoir Profiles



LAKE TAWAKONI IN THE MAIN LAKE NEAR THE DAM



LAKE TAWAKONI IN WACO BAY EQUIDISTANT FROM FINGER AND SPRING POINTS



LAKE TAWAKONI AT SH276

Segment 0507

